marine

HERTZ

hertz-audio.com



HMR 15



SPECIFICATION

DISPLAY	2.8" DOT Matrix display	
PEAK POWER @ 4 Ω	4 x 50 W	
FRONT PANEL IP RATING	IP66	
LINE OUTS	2x L+R (Front and Rear)	
SUBWOOFER OUT (RCA)	1x L+R (LPF: 80, 120,160 Hz)	
AUX INPUT (RCA)	1x L+R	
EQUALIZER	BASS-TREBLE	
EQ. PRESET	3	
CAMERA IN	-	
BATTERY VOLTAGE GAUGE	-	

SOURCES		
TUNER	HMR 15: AM/FM (EU/US) HMR 15 D: FM (RDS*) (EU) *where available	
USB	Yes (1A)	
IPOD/IPHONE	-	
DAB+ Ready	AB+ Ready -	
SIRIUS™ READY	-	
NMEA 2000 READY	-	
BLUETOOTH	5.0	
BLUEIOOIH	Audio streaming	
REMOTE CONTROL	EMOTE CONTROL HMC U1 (up to 3)	
SIZE & MOUNTING		
Unit Size mm (in.) W 126 (4.960) × H 114 (4.488) × D 96.5 (3.799)		
Mounting Hole size mm (in.) Ø 89.5 (3.52)		

72 (2.83)

Panel mount (4 screws); U-Bracket











PURE MARINE DESIGN

HMR 15 features IP66 protection grade, ASTM-D4329 standards for UV resistance and ASTM-B117 for salt fog operability, giving you unstopped pleasure season after season.

CONNECTIVITY









KEY FEATURES



- 3 EQ preset created by Hertz audio engineer
- Minimalist square-shaped design, perfectly in line with the latest trends in the most prestigious navigation instruments.
 Generous display with the large marine-grade pushbutton panel
 Bluetooth® 5.0 to stream high quality audio from your favorite mobile device



Mounting Depth mm (in.)

Mounting Method



HMC U1 OPTIONAL REMOTE CONTROL Play your favorite song and pump-up the volume while swimming in open water. Thanks to IPX7 certification

A	126 mm	4.96 in.
В	114 mm	4.49 in.
C	70,8 mm	2.79 in.
D	25,7 mm	1 in.
E	89.5 mm	3.52 in.





