

CHORUS 826 V

Product specification sheet

Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz, ready for SACD.

6 1/2" (165mm) Polyglass midrange.
Highly dynamic and detailed medium.

2 x 6 1/2" (165mm) Polyglass woofers.
Very high power handling, more bass.

Front-firing port for bass impact.

Powerflow™ multiport system.
Powerful bass.

Down-firing port for deep bass.

Acrylic body, black mirror effect.
Exclusive finish.

Solid MDF construction
up to 1" (25mm) width.
Non parallel inner wall structure.

OPC crossover.
Perfect staging.
New insulated Focal terminals.

Cast Aluminum base.
Stable base.
Adjustable spikes with key.



- ◆ High-end design, affordable luxury
- ◆ Speakers designed and manufactured by Focal
- ◆ A sound quality never seen before at this price level
- ◆ Acrylic body, 2 side finishes; Ebony and Natural

Standard finishes of the sides



Ebony (satin) Natural (matte) Acrylic body

Type	3-way bass-reflex floorstanding loudspeaker
Drivers	2x6 1/2" (165mm) Polyglass woofers 6 1/2" (165mm) Polyglass midrange 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	45Hz - 28kHz
Low frequency point (- 6dB)	37Hz
Sensitivity (2.83V/1m)	91.5dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	2.9 ohms @ 118Hz
Max. power handling.	220W
Power RMS	150W
Crossover frequency	300Hz / 3kHz
Dimensions (HxWxD)	40 7/8" x 11 1/8" x 14 3/4" (1038x282x375mm)
Net weight	56.8lbs (25.8kg)

The star floor-stander of the series combines power from its two woofers, Powerflow™ system and separate midrange. The **Chorus 826 V** is a very classy speaker, untiring even whilst copiously performing in rooms up to 40 m².



FOCAL
the Spirit of Sound